

## TEMPEST LCD Displays DTD-17T, 214T, 400T, 460T High Performance & Security



TEMPEST displays from CIS are designed to support multiple applications including personal computing, video, collaboration, and presentation. The 40 & 46 inch versions have built in network, keyboard, and mouse capabilities for image sharing and web browsing and have optional speakers.

- Shown
- DTD-17T 17" LCD Display
  - DTD-214T 21.3" LCD Display
  - DTD-400T 40" LCD Display
- Not Shown
- DTD-460T 46" LCD Display

**Built & Tested to meet the following TEMPEST standards:**

- NSTISSAM 1-92 Level I
- AMMSG 720B

**DTD-17T**

- Contrast Ratio
- 400:1
- Max Resolution
- 1600 x 1200
- Input
- 15pin VGA
- Power
- 110-240VAC auto sensing
- Dimensions
- 15.5"W x 13.5"H x 2.75"D
- 10"x10" Base adds 1.5"H
- Weight
- 16.15 lbs

**DTD-214T**

- Contrast Ratio
- 900:1
- Max Resolution
- 1600 x 1200
- Input
- 15pin VGA
- Power
- 110-240VAC auto sensing
- Dimensions
- 19.5"W x 16.0"H x 2.75"D
- 10"x10" Base adds 1.5"H
- Weight
- 25.15 lbs

**DTD-400T**

- Contrast Ratio
- 1200:1
- Max Resolution
- 1366 x 768
- 256 RGB levels, 16.7M colors
- Horizontal Freq. 30-70kHz
- Vertical Freq. 50-85 Hz
- Inputs/Outputs
- 15pin VGA
- S-Video (optional)
- USB (optional)
- Audio (for optional speakers)
- 100MB Fiber SC Ethernet (optional)
- Power
- 110-240VAC auto sensing
- Dimensions
- 39.5"W x 24"H x 5.5"D
- 16" Base stand adds 1"H
- Weight
- 82.75 lbs

**DTD-460T**

- Contrast Ratio
- 1200:1
- Max Resolution
- 1366 x 768
- 256 RGB levels, 16.7M colors
- Horizontal Freq. 30-70kHz
- Vertical Freq. 50-85 Hz
- Inputs/Outputs
- 15pin VGA
- S-Video (optional)
- USB (optional)
- Audio (for optional speakers)
- 100MB Fiber SC Ethernet (optional)
- Power
- 110-240VAC auto sensing
- Dimensions
- 41.5"W x 25.5"H x 5.5"D (est.)
- 16" Base stand adds 1"H
- Weight
- 89.15 lbs (est.)

Warranty is One Year Parts and Labor