

TEMPEST 2811 Cisco Router/Switch DTD-2811T Cisco Technology – TEMPEST Security



Built and tested to meet the following TEMPEST standards:

- NSTISSAM 1-92 Level I
- AMSG 720B

Powered by Cisco IOS® Software, the DTD-2811-T is a TEMPEST Cisco 2800 series router providing an efficient solution with a comprehensive feature set in a compact design. The Cisco 2800 Series features the ability to deliver multiple high-quality simultaneous services at wire speed up to multiple T1/E1/xDSL connections. The routers offer embedded encryption acceleration and on the motherboard voice digital-signal-processor (DSP) slots; intrusion prevention system (IPS) and firewall functions; optional integrated call processing and voice mail support; high-density interfaces for a wide range of wired and wireless connectivity requirements; and sufficient performance and slot density for future network expansion requirements and advanced applications. Highly configurable with an array of options, the DTD-2811T TEMPEST version is a 2 U device with front and rear rack mounting supports and a rugged chassis.

Founded on 20 years of leadership and innovation, the Cisco® 2800 Series of integrated services routers (refer to Figure 1) intelligently embed data, security, voice, and wireless services into a single, resilient system for fast, scalable delivery of mission-critical business applications. The unique integrated systems architecture of the Cisco 2800 Series delivers maximum business agility and investment protection.

Configuration Information:

Supports all 2800 Series Software and Modules

Ordering and Information:

Call for quote



Front Panel Console Port Access



Flexible Rear Panel Port Capacity

Dimensions and Weight

17.5"W x 3.5"H x 22"D, 15 – 18 lbs depending on configuration

Power

AC input voltage: 100 to 240 VAC

Frequency: 47 to 64 Hz

- Warranty is one year, parts and labor